



Desktop Laser Labels Fluorescents

PRODUCT SPECIFICATIONS

PRODUCT DESCRIPTION:

A 60# fluorescent facestock in a variety of colors for attention getting, permanent applications. Our fluorescents are designed for excellent image quality and processing in most desktop laser printers.

FACESTOCK PROPERTIES:

A 60# fluorescent facestock specially engineered for low speed laser printing.

Caliper: 4.2 mil +/- 10%

Basis Weight: 60# +/- 10%

ADHESIVE PROPERTIES:

A general purpose, permanent acrylic emulsion adhesive, characterized by excellent ultimate adhesion to a wide variety of substrates. MP-910 adhesive is a patented formula designed to eliminate virtually all sheet edge adhesive bleed.

Temperature Ranges:

Min. Application Range: 40°F

Service Range: -65°F - 200°F

LINER PROPERTIES:

A 2.5 mil liner displaying excellent internal strength, toughness and tear resistance. The liner is specifically designed for roll-to-sheet applications.

Caliper : 2.5 mils +/- 10%

Basis Weight: 40# +/- 10%

APPLICATIONS AND USES:

Typical applications are color-coding, warning, express, special pricing and point-of-purchase display labels.

SHELF LIFE:

One year when stored at 72°F and 50% relative humidity in proper packaging.