

# Specification Sheet Z-Select 4000T

#### Features:

- Thermal transfer, premium, ultra smooth, paper label with a permanent acrylic adhesive
- Excellent high speed print quality
- Meets FDA 175.105 for indirect food contact requirements
- Available in white (05210RM)

## **Suggested Applications:**

- Labeling of packaging material including corrugate, plastic, and metal
- Product identification
- Compliance labeling
- Work in process labeling
- Food labeling

#### **Material Construction:**

	Description	Caliper
Facestock	White smooth topcoated paper	2.7 mil
Adhesive	High performance, acrylic-based	0.5 mil
Liner	40 lb. semi-bleached, kraft stock	2.5 mil
	To	tal 5.7 mil +/- 10%

### **Temperature Performance:**

• Minimum Application Temperature: 25° F (-4° C)

• Service Temperature: -65° F to 200° F (-54° C to 93° C)

• Storage Conditions: 32° F to 70° F (0° C to 21° C) at 35% to 50% RH

Expected Exterior Life
Not recommended for outdoor use

Revised 11/14/08





# Specification Sheet Z-Select 4000T

# **Suggested Ribbons for Applications with Chemicals**

	Weak				Moderate				Harsh			Extreme					
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
2000			Χ	Χ	Х												
2100			Χ	Χ	Χ												
5319			Х	Χ	Х												
3200			Χ	Χ	Х												

### 180° Peel Room Temperature Peel Adhesion (oz/in):

Corrugate		Ste	eel	Polyca	rbonate	Polyethylene			
5 min	24 hr	5 min	24 hr	5 min	24 hr	5 min	24 hr		
14	19	*	*	*	*	35	*		

<sup>\*</sup>Attraction between adhesive and surface is so great that the facestock rips.

NOTE: For guidance only, not to be used for setting specifications

## **Product Performance and Suitability**

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

Revised 11/14/08