



# ***Specification Sheet***

## ***Z-Select 4000T 7.0 mil Tag***

### **Features:**

- Thermal transfer, premium, topcoated, ultra smooth, 7.0 mil paper tag
- Excellent high speed print quality
- Topcoating is suitable for fanfolding
- Available in white (05209RM)

### **Suggested Applications:**

- General-purpose ticketing
- Retail hang tags
- Inventory control and shop floor tracking tickets
- Work in process tags

### **Material Construction:**

Description		Caliper
Facestock	White smooth topcoated paper tag	7.0 mil
		<b>Total</b> 7.0 mil +/- 10%

### **Temperature Performance:**

- Minimum Application Temperature: NA
- Service Temperature: -40° F to 200° F (-40° C to 93° C)
- Storage Conditions: 32° F to 70° F (0° C to 21° C) at 35% to 50% RH
- Expected Exterior Life: Not recommended for outdoor use





# **Specification Sheet**

## **Z-Select 4000T 7.0 mil Tag**

### **Suggested Ribbons for Applications with Chemicals**

	Weak					Moderate				Harsh			Extreme				
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
<b>2000</b>			X	X	X												
<b>2100</b>			X	X	X												
<b>5319</b>			X	X	X												
<b>3200</b>			X	X	X												

NOTE: For guidance only, not to be used for setting specifications

### **Product Performance and Suitability**

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

