



Specification Sheet

Z-Select 400T Removable

Features:

- Thermal transfer, premium, ultra smooth, paper label with a removable acrylic adhesive
- Excellent high speed print quality
- Topcoating is suitable for fanfolding
- Meets FDA 175.105 for indirect food contact requirements
- Available in white (05233RM)

Suggested Applications:

- Product identification
- Labeling of shelves, bins, or totes intended for reuse when label is removed
- Work in process labeling

Material Construction:

	Description	Caliper
Facestock	White smooth topcoated paper	3.2 mil
Adhesive	Removable, acrylic-based	0.8 mil
Liner	40 lb. semi-bleached, kraft stock	2.5 mil
	Total	6.5 mil +/- 10%

Temperature Performance:

- Minimum Application Temperature: 40° F (4° C)
- Service Temperature: -65° F to 180° F (-54° C to 82° C)
- Storage Conditions: 32° F to 70° F (0° C to 21° C) at 35% to 50% RH
- Expected Exterior Life: Not recommended for outdoor use





Specification Sheet

Z-Select 400T Removable

Suggested Ribbons for Applications with Chemicals

	Weak					Moderate				Harsh			Extreme				
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
2000			X	X	X												
2100			X	X	X												
5319			X	X	X												
3200			X	X	X												

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

